



US006618713B1

(12) **United States Patent**
Woodall

(10) **Patent No.:** **US 6,618,713 B1**
(45) **Date of Patent:** **Sep. 9, 2003**

(54) **NEURAL DIRECTORS**

(75) **Inventor:** Roger L. Woodall, Jewett City, CT (US)

(73) **Assignee:** The United States of America as represented by the Secretary of the Navy, Washington, DC (US)

(*) **Notice:** Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) **Appl. No.:** 09/436,957

(22) **Filed:** Nov. 4, 1999

(51) **Int. Cl.⁷** G06F 15/18

(52) **U.S. Cl.** 706/15

(58) **Field of Search** 706/15-44

(56) **References Cited**

U.S. PATENT DOCUMENTS

5,712,959 A • 1/1998 Streit 706/20
5,724,487 A • 3/1998 Streit 706/25
5,790,758 A • 8/1998 Streit 706/33

OTHER PUBLICATIONS

An adaptive training algorithm for back-propagation neural networks, Hsin, H.-C.; Li, C.-C.; Sun, M.; Scabassi, R.J.; Systems, Man and Cybernetics, 1992., IEEE International Conference on , 18-21, Oct. 1992, pp. 1049-1052 vol. 2.*

An adaptive training algorithm for back-propagation neural networks Hsin-Chin Hsi; Ching-Chung Li; Mingui Sun; Scabassi, R.J.; Systems, Man and Cybernetics, IEEE Transactions on , vol.: 25 Issue: 3 , Mar. 1995 pp. 512-514.*
ANSA: a new neural net based scheduling algorithm for high level synthesis Kemal Unaltuna, M.; Pitchumani, V.; Circuits and Systems, 1995. ISCAS '95., 1995 IEEE International Symposium on , vol. 1, (1995) pp. 385-388.*

* cited by examiner

Primary Examiner—John Follansbee

Assistant Examiner—Michael B. Holmes

(74) *Attorney, Agent, or Firm*—James M. Kasischke; Michael F. Oglo; Jean-Paul A. Nasser

(57) **ABSTRACT**

A neural director is provided which is a neural network constructed with weights that are determined a priori. The neural director receives an input vector X comprising "I" input components " X_i " and generates in response an output vector Y comprising "J" output components. The neural director has an input processing node layer which receives the input vector X and an output processing node layer which generates the output vector Y. The connections between the input and output processing node layers are a unique weighting set $w(i,j)$ that contains an internal representation of a uniform spatial distribution of "J" unit vectors throughout a unit sphere of "I" dimensions. Thus the cosine value between any two adjacent unit vectors is a constant everywhere in the unit sphere.

17 Claims, 3 Drawing Sheets

